

Battery electric vane self-priming pump 12 or 24V direct electricity, constituted by cast iron body, sintered steel impeller and acetyl resin vane. Built-in by-pass valve and stainless steel filter.



## Battery electric pump 45 l for diesel transfer equipped with:

Power cable 2 m length sec. 2,5 mmq with pincers and fuse

Power cable 4 m length sec. 4 mmq with pincers and fuse

Self-priming rotary electric pump

Cast iron body

By-pass valve

DC engine

Stainless steel filter 100 micron

Motor protection rating IP55

Ref.	Flow rate	Voltage	Power	Electricity	Cable lenght	Inlet-Outlet	Duty cycle	Max suction height	Weight	Packaging
	l/min	DC Volt	W	A	m	BSPG	min	m	kg	mm

<b>091-5080-045</b>	<b>45</b>	12	264	18	2	F 1"-F 1"	40	3	5,10	250X195X210
<b>091-5081-045</b>	<b>45</b>	12	264	18	4	F 1"-F 1"	40	3	5,10	250X195X210
<b>091-5082-045</b>	<b>45</b>	24	312	10	2	F 1"-F 1"	40	3	5,10	250X195X210
<b>091-5083-045</b>	<b>45</b>	24	312	10	4	F 1"-F 1"	40	3	5,10	250X195X210

## Dimensions:

